



# L.

## Paints and Coatings

# L.01

## Exterior Timber Paint

---

### ***Function***

- To be used (ONLY) on timber furniture and elements that are currently painted.
- All new timber to be oiled.

### ***Supplier***

- Contractor to nominate based on below specifications.

### ***Finish***

- Dulux Weathershield Acrylic Low Sheen
- Various existing colours. Refer to Maintenance and Construction Coating Schedule for specific colours, maintenance

### ***Installation***

- Refer to manufacturers instructions.

### ***Maintenance***

- Under review

# L.02

## Exterior Timber Stain

---

### ***Function***

- To be used (ONLY) on timber furniture and elements that are currently stained.
- All new timber to be oiled.

### ***Supplier***

- Contractor to nominate based on below specifications.

### ***Finish***

- Dulux – Intergrain Natural Stain
- Colour selection to match the furniture/ element stain

### ***Installation***

- 3 stage process. Refer to manufacturers instructions.

### ***Maintenance***

- Under review

# L.03

## Exterior Timber Clear Oil

---

### **Function**

Clear oil coating for timber decking, seats and furniture adjacent to planting such as along the Coastal walk.

### **Supplier**

- Contractor to nominate based on below specifications.

### **Finish**

*Dulux – Intergrain Nature’s Timber Oil*

### **Installation**

- Suitable for use adjacent to vegetation.
- Refer to manufacturers instructions.

### **Maintenance**

- Under review

# L.04

## Exterior Metal Paint

---

### **Function**

- Micaceous Iron Oxide (MIO) is to be used on balustrades, fences and gates where there is limited physical contact i.e. Not as a handrail.
- Use where the surface will have low levels of wear and tear and is unlikely to be marked.

### **Supplier**

- Contractor to nominate based on below specifications.

### **Finish**

Dulux MIO Colour: Bridge Grey

### **Installation**

- Refer to manufacturers instructions.

### **Maintenance**

- under review

# L.05

## **Paving Sealant**

---

### ***Function***

- To protect and treat unit pavers from the ingress of water and water borne chemicals.

### ***Supplier***

- Contractor to nominate based on below specifications.

### ***Finish***

- Silane-siloxane penetrating sealant.
- The sealant should be solvent based silane-siloxane penetrating sealer designed to protect both horizontal and vertical surfaces from the ingress of water and salts.
- It should have a low VOC content.
- It should be water repellent, such that the water will bead on the surface of the concrete paver.
- It should not alter the colour of the surface ensuring a natural look is retained.

### ***Installation***

- Apply in two coats as per manufacturer's instructions
- Ensure the sealant is not applied on damp or wet surfaces.
- The sealed surface should be protected from moisture for a minimum of six hours after application.

### ***Maintenance***

- TBC

# L.06

## **Anti-Graffiti Wall Sealant**

---

### ***Function***

- For use on walls

### ***Supplier***

- TBC

### ***Finish***

- TBC

### ***Installation***

- TBC

### ***Maintenance***

- TBC

This page is intentionally left blank



WAVERLEY  
COUNCIL